



INTERIOR

Briza

**SPLENDOUR
EMULSION**



PRODUCT DESCRIPTION

Naturelite 'Briza' Emulsion is a superior quality water based paint with smooth silky effect for interior applications. Due to its modern technology formulation the paint has an excellent adhesion as well as very good washability with water detergents. Naturelite Briza prevents stains from penetrating, offers maximum resistance to water streaking and spotting features remarkable hide and covers dark colors. With exceptional coverage and washability, it is an excellent product for any room in your home. As the technology advantage, the product has born with green, low VOC and truly intake friendly paint with exceptional qualities for the interior surfaces, and which is compatible with the highest global requirement for maintaining the environment.



GREEN ADVANTAGES

LOW ODOUR

LOW VOC

APEO FREE

PHTHALATES FREE

NO ADDED FORMALDEHYDE

NO ADDED LEAD

NO ADDED AMMONIA

NO ADDED ARSENIC

NO ADDED CHROMIUM

NO ADDED CADMIUM

RECOMMENDED USAGE:

Naturelite Briza recommended to use as a finish coat on concrete, cement, gypsum, hard board and brick surfaces for interior applications, where easy clean is required such as hotels, hospitals, airports, schools, houses, palaces, residential complexes and any populous places.

PHYSICAL PARAMETERS:

Finish	:	Silky Smooth Finish
Colour	:	Produced in White and other colors of Naturelite Paints Color shades.
Coverage/Spread Rate	:	280-330 Sq.Feet / Liter/Coat @17.5 Micron DFT 140-165 Sq.Feet/Liter/Coat @ 35 Micron DFT

Actual Coverage may vary depends upon the application and surface conditions.



DRYING TIME

Surface Dry	:	1 Hour
Full Dry	:	4 Hours
Recoating Interval	:	8 Hours (Minimum)

The above results according to ASTM D5895@25°C

Stability of Thinned Paint : Use within 24 Hours

VOC in grams : < 5 Grams / Ltr



Dry Film Thickness



Brush : 20-25 microns



Roller: 30-35 Microns

 Washable	High
--	------

SHELF LIFE



In sealed Container :  24 months in a dry, cool and well ventilated place.

Surface Preparation & Application Details

- All new surfaces must be cured at least for 30 days prior to surface preparation for paint applications.
- Remove old paint from surfaces completely. Make sure the surface is clean, dry, free from dust, oil, grease, salt & mold.
- Apply single coat of Naturelite primer and wait for its drying time of 6-8 hours.
- Use Naturelite Wall Putty to the dents, pores and cracks for smoothening the surfaces and wait for 4-6 hours.
- Sand the surfaces using emery paper 180 and clean the surfaces from dust.
- Apply another coat of Naturelite primer and use Emery paper 320 and make sure the surface is free from dust.
- Finally Apply two coat of BRIZA INTERIOR EMULSION with an interval of 8 hours drying time can provide a better result, an extra coat may be used for dark shades if needed
- Surface temperature required during application must not be less than 10°C; the surface moisture should not exceed 8% and the relative humidity at work place not to exceed 70%.

WATER DILUTION DETAILS:



Recommended Water : Drinking water.

Dilution ratio:



Spray Gun : 15 - 30 % by volume. (Depends on weather conditions at work place)



Roller : 10 - 15 % By volume. (Depends on weather conditions at work place)

PACK SIZES:



AVAILABLE COLOR SHADES:



Shades as per Naturelite Color Fandek.

Application Tools:



Spray Gun : Recommended nozzle size : 1.5-1.8mm



Roller : Recommended Type : Soft and smooth woolen roller.



Brush : General / Normal type

SAFETY PRECAUTIONS:

During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapour, should be strongly avoided. When working with paint sufficient ventilation, forced ventilation should be provided. For spray application system, eye, skin, respiratory protection are always recommended. Keep away from the reach of children.

