

Minte Super Kleen



PRODUCT DESCRIPTION

Naturelite Minte Super Kleen interior emulsion is a 100% acrylic paint designed for trims and accents, offering a tough, washable, finish ideal for high-contact surfaces. Its advanced stain – release technology with cross linking polymers resists penetration, allowing easy removal of everyday stains and with just soap and water- keeping walls fresh and clean for years. Certified under Naturelite’s Green Assured standards, it promotes a safer, eco-friendly interior environment.



- GREEN ADVANTAGES**
- Low odour
 - Low VOC
 - APEO free
 - Phthalate free
 - No added Mercury
 - No added Ammonia
 - No added Lead
 - No added Arsenic
 - No added chromium
 - No added Cadmium

RECOMMENDED USAGE:

Naturelite Minte Super Kleen is recommended to as finish coat on concrete, cement, gypsum, hard board and brick surface for interior application where easy clean is required such as hotels, hospitals, airports, schools, palaces, residential complexes, kids room and any other populous places.

PHYSICAL PARAMETERS:

Colour	:White
Finish	: Ultra sheen
Coverage/ spread rate	: On normal masonry surface after brushing 200-240ft ² /L for 1 coat 110-120 ft ² /L for 2 coats

Actual coverage may vary depends upon the application and surface conditions.



DRYING TIME

Surface dry : 30minute

Full dry : 4 hours

Recoat interval : 4-6 hours

Stability of thinned paint : Use within 24 hours

The above results according to ASTM D 5895@ 25°C

VOC in grams : <5grams/L



SHELF LIFE

36 months from the date of manufacturing, if it is stored under proper conditions and in its original container.

Surface Preparation & Application Details

Surface preparation:

Ensure the substrate is clean and free from oil, grease or any other loosely held particles.

Priming:

After cleaning apply one coat Naturelite interior primer as per the data sheet. Fill any cracks present with Naturlite Care Plus WP crack Fill and smoothen the surface with Naturelite Wallputty. Then apply second coat of Naturelite interior wall primer. Light sand with emery 320 and make sure surface is free from dust.

Application

Topcoat Application:

Apply two coats of Naturelite Minte Super Kleen with recommended dilution in an interval of 4-6 hours using brush/roller/gun. An extra coat may be used if needed.

WATER DILUTION DETAILS:



Recommended Water : Drinking water.

Dilution ratio:



Spray gun – 50-55% by volume



Brush/roller – 40-50 % by volume
(Depends on weather conditions at work place)

Application Tools:



Spray gun : Recommended nozzle size 1.5-1.8mm



Roller : Recommended type soft and smooth woollen roller



Brush : General/normal type

PACK SIZES:



1 Ltr



4 Ltrs



10 Ltrs



20 Ltrs

AVAILABLE COLOR SHADES:



Shades as per Naturelite Color Fandek.

SPECIAL INSTRUCTIONS

- Surface temperature required during application must not be less than 10°C, the surface moisture should not exceed 8% and relative humidity at work place not exceeds 70%.
- Early removal of stains will give best result. Degree of stain removal may vary depending on nature of stain.
- Remove stains with soft cloth or sponge soaked in soap solution. Then immediately wipe it with water to prevent spreading of stain.

SAFETY PRECAUTIONS

During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapour; should be strongly avoided. Keep away from reach of children. It is recommended to wear mask during sanding and surface preparation to avoid dust inhalation.

